


MSHA's Accident Prevention Program Safety Idea

Safety and Health are Values!

Auxiliary Power Source Interlocks

A failsafe mechanically operated electrical interlock on motor-generator auxiliary power sources can prevent fatal electrical shocks.





failsafe mechanically operated electrical interlock on the motor-generators supplying power to the auxiliary power sources can prevent harmful or fatal electrical shocks. A failsafe mechanically actuated electrical interlock system prevents the main and auxiliary power sources from being connected to the same circuit at the same time. It requires a positive action that must be performed to start the motor-generator and opens all other circuits except the motor-generator auxiliary power source. An idea for such an interlock is attached.

MOTOR-GENERATOR INTERLOCK CIRCUIT

Motor-generator sets are frequently used for auxiliary power sources onboard draglines and other large equipment. Figure 1 is an idea that creates a failsafe mechanical/electrical interlock that can prevent an auxiliary power source such as a motor-generator set and the main power source from being connected to the same circuit at the same time.




Figure 1

Contacts S_1 are mounted in the ignition circuit of the diesel engine and are mechanically actuated <u>only</u> by the linkage of the main input circuit breaker or switch as it is opened. When the main switch opens, the linkage closes the S_1 contacts, and <u>only</u> then can the diesel engine be started and the auxiliary circuit breaker closed. When so installed, a motor-generator set cannot be started and energized unless the machine main circuit breaker or switch is in the open position. Thus a positive action (i.e. opening the main input switch) is established that must be taken before the auxiliary power source can be energized.